



## Cuscinetti a sfera fila unica 7518-DL-NICE - 7518-DL-NICE

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/fila-unica/7518-dl-nice>

**7500 Series™ Heavy Duty Precision Ground Radial Bearings** 

- PRECISION GRINDING ON ALL CONTACT SURFACES - GRINDING TO THE 100 MICROMETER FINISH
- EASY TO USE HIGH DIMENSIONS
- MEDIUM LOADS
- HIGH SPEED RANGE - 5000 - 10000 RPM
- THERMALLY TREATED BEARING STEEL
- ANTI-CORROSION
- WIDE RETAINER STANDARDS
- DOUBLE SEALED VERSIONS
- EXCELLENT OPERATING TEMPERATURE CONTACT ROLL WITH TIGHT TOLERANCES
- AVAILABLE IN BOTH BEALED OR OPEN
- ALL BEARINGS HAVE A PUMP AND COOLANT HOLES AVAILABLE TO BE ORDERED
- RECOMMENDED FOR APPLICATIONS WHERE CORROSION, SHOCK AND VIBRATION ARE CONCERNS



BEARING	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	INNER WIDTH C (in) (mm)	F (in) (mm)
7518™	+0.000 -0.005 -0.015	+0.000 -0.005 -0.015	+0.000 -0.005 -0.015	0.0625 1.59	0.8750 22.23	1.872 42.47

PRINCIPLE DIMENSIONS			BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS			
G (in) (mm)	H (in) (mm)	J (in) (mm)	Dynamic C (lb) (N)	Static C <sub>0</sub> (lb) (N)	W lb (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)	
0.190 4.83	0.065 1.65	2.7806 70.25	0.035 0.89	5360 23852	2620 11659	0.80 0.36	1.375 34.93	2.312 58.72	0.036 0.89

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG)  
 ② Tolerances for 7514™ and larger is +0.000/-0.005 (+0.001/-0.125)  
 ③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear  
 ④ Weights given are for greased and sealed versions  
 All bearing designations listed herein are trademarks of FSC Nippon Bearings.

## CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3616060473325
Diametro interno	28.58 mm
Diametro esterno	65.09 mm
Spessore	19.05 mm
Peso	360 g
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE