

Cuscinetti a sfera fila unica 400-23V-NICE - 400-23V-NICE

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/fila-unica/400-23v-nice>

400 Series® Single Row Unground Radial Bearings **NICE**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm) +0.0005-0.000 +13/-00	B O.D. (in) (mm) +0.005-0.000 +13/-00	C WIDTH (in) (mm) +0.010-0.010 +25/-25	D WIDTH (in) (mm) Reference	No.	Size (mm)
400™	23V	0.312 7.92	1.281 32.54	0.312 7.92	0.312 7.92	16	5/32 3.97

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)
0.09 0.04	275 1224	180 800	133 588	107 476	75 334	52 231

Notes
Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3663952560076
Diametro interno	7.92 mm
Diametro interno	0.312" inch
Diametro esterno	32.54 mm
Diametro esterno	1 9/32" inch
Spessore	7.92 mm
Spessore	0.312" inch
Peso	40 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE