


## Cuscinetti a sfera fila unica 5418-V-NICE - 5418-V-NICE

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/fila-unica/5418-v-nice>

**5000** Series® Single Row Unground Flanged Radial Bearings (con't) **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE HIGH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- FLANGE ON O.D. LOCATES BEARING IN TUBE OR HOUSING
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA						
		BORE A (in) (mm)	O.D. B (in) (mm)	WIDTH C (in) (mm)	D (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm)
5418™	V	1.000 +0.005/-0.000 25.40	2.069 +0.005/+0.000 52.50	0.572 +0.010/-0.010 14.53	0.980 2.36	2.125 53.98	0.218 5.54	0.718 +0.010/-0.010 18.34

BALLS (in) (mm)	W (lbs) (kg)	RADIAL CAPACITY						
		REVOLUTIONS PER MINUTE						
NO.	SIZE	50 (in)	100 (in)	200 (in)	300 (in)	600 (in)	1200 (in)	
17	1/4 6.35	0.30 0.14	757 3389	525 2338	362 1611	293 1304	204 908	142 632

Notes: Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft  
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

### CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3663952560328
Diametro interno	25.4 mm
Diametro esterno	50.8 mm
2° Diametro esterno	53.98 mm
Spessore	14.53 mm
secondo spessore	18.24 mm
Peso	140 g
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE