

Cuscinetti a sfera fila unica 616-V-NICE - 616-V-NICE

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/fila-unica/616-v-nice>

600 Series™ Unground Thrust Bearings (con't) **NICE**

- UNGROUND THRUST BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1300 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- SOFT STEEL BAND OFFERS EASE OF INSTALLATION
- UPPER RING IS FREE TO ROTATE AND HAS LOOSE FIT FOR SHAFTS
- LOWER RING IS FIRED AND HAS SHAFT CLEARANCE IN THE BORE



BEARING DIMENSIONAL DATA							
BEARING	SUFFIX	A	A1	B	C	BALLS	WEIGHT
		BORE (in) (mm)	BORE (in) (mm)	O.D. (in) (mm)	HEIGHT (in) (mm)		
616™	V	+0.010-0.000 +0.25-1.00 31.75	+0.010 +0.25 52.93	+0.010 +0.79 59.53	+0.010 +0.25 15.88	23 1/4 6.35	0.4 0.18

THRUST CAPACITY					
REVOLUTIONS PER MINUTE					
10 (lbs) (N)	50 (lbs) (N)	100 (lbs) (N)	250 (lbs) (N)	500 (lbs) (N)	1000 (lbs) (N)
1794 7983	1449 6448	1069 4757	579 2577	419 1865	298 1326

Notes
Balls - Carbon Steel Grade 520
Washers - Carbon Steel Case Hard
Bands - Carbon Steel Soft
Bearings Oiled with a Rust Preventative
All Bearings Marked on Band with "Designation Nice USA" as Shown

CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3663952560496
Diametro interno	31.75 mm
Diametro interno	1 1/4" inch
Diametro esterno	59.53 mm
Diametro esterno	2 11/32" inch
Spessore	15.88 mm
Spessore	5/8" inch
Peso	180 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE