

Cuscinetti a sfera fila unica 518-NICE - 518-NICE

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/fila-unica/518-nice>

500 Series® Single Row Unground Combination Radial and Thrust Bearings (con't)

NICE®

- ANGULAR CONTACT UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY

BEARING	BEARING DIMENSIONAL DATA										COMBINED RADIAL					
	A	B	C	D	E	R	BALLS	WEIGHT (lbs) (kg)	REVOLUTIONS PER MINUTE							
	(in) (mm)	(in) (mm)	(in) (mm)	(in) (mm)	(in) (mm)	(in) (mm)	No. Size		10	50	100	250	500	1000		
518	1.312 T10 33.33 T10	2.3075 T10 58.611 T10	0.600 15.48	0.531 13.49	1.844 46.82	0.234 5.95	19 9/32	0.30 7.14	630 2804	420 1869	442 1967	295 1313				

AND THRUST CAPACITY								THRUST CAPACITY							
REVOLUTIONS PER MINUTE								REVOLUTIONS PER MINUTE							
100	250	500	1000	10	50	100	250	500	1000	10	50	100	250	500	1000
R (lbs) (N)	T (lbs) (N)	R (lbs) (N)	T (lbs) (N)	R (lbs) (N)	T (lbs) (N)	R (lbs) (N)	T (lbs) (N)	R (lbs) (N)	T (lbs) (N)	R (lbs) (N)	T (lbs) (N)	R (lbs) (N)	T (lbs) (N)	R (lbs) (N)	T (lbs) (N)
312	208	199	130	139	93	99	66	625	905	373	217	156	130	1398	828

Ⓢ Maximum fillet radius on shaft which the bearing will clear
 Ⓢ SPECIAL TOLERANCES
 TR = +0.008-0.000 (+20F-00)
 T10 = +0.010-0.000 (+25F-00)

Note:
 Balls - Carbon Steel Grade 200
 Rings - Carbon Steel, Case Hardened
 Bands - 1010 Carbon Steel, Sulf
 Bearings supplied prelubricated with grease

CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3663952560656
Diametro interno	33.33 mm
Diametro esterno	58.611 mm
Spessore	15.48 mm
Peso	140 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE