

Accessorio de supporti 7608-DL-NICE - 7608-DL-NICE

<https://www.123cuscinetti.ch/cuscinetti-supporti/supporti/accessorio/7608-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings With Extended Inner Ring **NICE**

- PRECISION GRINDING ON ALL CONTACT SURFACES - FINISH TO THE 7th BEARING-
- EASY TO USE INCH DIMENSIONS
- MEDIUM LOAD
- MAX SPEED RANGE: 5000-8000 RPM
- TIMOTHON HARDENED
- STEEL BEARING
- STYLISH CASE STANDAARD
- SHOULD BE OILED
- EXCELLENT APPARENT ANGLE OF CONTACT
- AVAILABLE SINGLE SEALER OR OPEN
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A SHIP FUL CRANK - THIS ONE CHANGED TO AN OPTION
- RECOMMENDED FOR APPLICATIONS WHERE EFFICIENCY, SILENCE AND RELIABILITY ARE REQUIRED.

BEARING Ø	PRINCIPLE DIMENSIONS					F (in) (mm)	G (in) (mm)
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	R (in) (mm)		
7608™	.5000 12.70	1.7500 44.27	0.6250 15.88	0.0625 1.59	1.009 25.63	0.138 3.45	

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C _d (lbf) (N)	Static C _s (lbf) (N)	W (lb) (kg)
0.042 1.07	1.922 48.82	1.992 50.61	0.405 10.29	0.233 5.92	10-32	0.036 0.89	2096 11548	1025 4561	0.38 0.16

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG) ② Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 ③ Tolerance for 7613™ and larger is +.0005-.0006 (+.0001-.015) ④ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of RBC Nice® Bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3616060473394
Diametro interno	12.7 mm
Diametro interno	1/2" inch
Diametro esterno	25.63 mm
Diametro esterno	1.009" inch
Spessore	15.88 mm
Spessore	5/8" inch
Peso	160 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE