


## Accessorio de supporti 7609-DL-NICE - 7609-DL-NICE

<https://www.123cuscinetti.ch/cuscinetti-supporti/supporti/accessorio/7609-dl-nice>

**7600** Series™ Heavy Duty Precision Ground Radial Bearings With Extended Inner Ring **NICE**

- PRECISION GRINDING ON ALL CONTACT SURFACES - SUBJECT TO THE BEARING DESIGNER'S CHOICE
- EASY TO USE INCH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 5000 - 8000 RPM
- TIMOTHY HARDENED
- STEEL BEARING
- STYLISH CASE STAMPING
- SHOULD BE OILED
- EXCELLENT APPLICABLE SINGLE LIP CONTACT
- AVAILABLE SINGLE BEARING OR OPEN
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A SHARP FILLET RADIUS - THIS WILL ENHANCE AS AN OPTION
- RECOMMENDED FOR APPLICATIONS WHERE SMOOTH, SILENT AND RELIABLE



BEARING Ø	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	F (in) (mm)	G (in) (mm)
7609™	.625 14.29	1.750 44.27	0.6250 15.88	0.0625 1.59	1.009 25.63	0.138 3.45

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C <sub>d</sub> (lbf) (N)	Static C <sub>s</sub> (lbf) (N)	W (lb) (kg)
0.042 1.07	1.922 48.82	1.982 50.00	0.405 10.29	0.233 5.92	10-32	0.036 0.89	2095 11548	1025 4561	0.34 0.15

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG)      ② Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear  
 ③ Tolerance for 7613™ and larger is +.0000-.0006 (+.0000-.015)      ④ Weights given are for greased and sealed versions  
 All bearing designations listed herein are trademarks of RBC Nice® Bearings.

## CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3616060473400
Diametro interno	14.29 mm
Diametro esterno	25.63 mm
Spessore	15.88 mm
Peso	150 g
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE