


Accessorio de supporti 7610-DL-NICE - 7610-DL-NICE

<https://www.123cuscinetti.ch/cuscinetti-supporti/supporti/accessorio/7610-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings With Extended Inner Ring **NICE®**

- PRECISION GRINDING ON ALL CONTACT SURFACES - FINISH TO THE TIER BEARING
- EASY TO USE INCH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 5000-8000 RPM
- TIMOTHY HARDENED
- STEEL BEARING
- STYLISH CASE STAMPING
- SHOULD BE OILED
- EXCELLENT APPARENT ANGLE OF CONTACT
- AVAILABLE SINGLE BEARING OR OPEN
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A SHARP FILLET
- EXCELLENT TOLERANCES TO ISO 48
- RECOMMENDED FOR APPLICATIONS WHERE EFFICIENCY, SILENCE AND RELIABILITY ARE REQUIRED.



BEARING Ø	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	F (in) (mm)	G (in) (mm)
7610™	.6250 15.88	1.7500 44.27	0.6250 15.88	0.0625 1.59	1.000 25.40	0.138 3.46

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C _d (lbf) (N)	Static C _s (lbf) (N)	W (lb) (kg)
0.042 1.07	1.922 48.82	1.922 48.82	0.405 10.29	0.233 5.92	10-32	0.036 0.89	2196 11548	1025 4581	0.32 0.15

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG) ② Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 ③ Tolerance for 7613™ and larger is +.0000-.0006 (+.0000-.015) ④ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of RBC Nice® Bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3616060473417
Diametro interno	15.88 mm
Diametro esterno	25.63 mm
Spessore	15.88 mm
Peso	150 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE