


Accessorio de supporti 7614-DL-NICE - 7614-DL-NICE

<https://www.123cuscinetti.ch/cuscinetti-supporti/supporti/accessorio/7614-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring (con't) **NICE®**

- PRECISION GRINDING ON ALL CONTACT SURFACES
- EASY TO USE DIMENSIONS
- MEDIUM LOADS
- HIGH SPEED RANGE: 5000 - 8000 RPM
- PRECISION MANUFACTURE
- SHOCK RESISTANT
- WIPER CASE STANDARD
- STANDARD SEALER STANDARD
- IDEALLY APPLICABLE ANGULAR CONTACT BEARING
- AVAILABLE SINGLE RINGS OR OPEN
- EXTENDED INNER RING WITH KEY GROOVES
- ALL BEARINGS HAVE A SHIP END OPTION - THIS PULLS OUTSIDE TO AN EXTENDED SEALING SURFACE
- RECOMMENDED FOR APPLICATIONS WHERE CORROSION RESISTANCE AND EXTENDED SEALING ARE REQUIRED



BEARING	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)		F (in) (mm)	G (in) (mm)
7614™	+0.0008 +0.000 -0.0000 -0.000	+0.0000 +0.000 -0.0005	+0.000 0.000	0.0025 1.58	1.308 33.17	+0.005 +0.13 -0.005 -0.13
	0.8750 22.23	2.0000 50.80	0.6250 15.88	0.0625 1.58		0.1306 3.45

PRINCIPLE DIMENSIONS							BASIC LOAD RATINGS		WEIGHT
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C (lb) (N)	Static C ₀ (lb) (N)	W (lb) (kg)
0.042 1.07	2.158 54.77	1.179 29.95	0.492 12.50	0.261 6.63	1/4-28	0.039 0.99	2970 13217	1350 6098	0.43 0.20

When ordering please indicate bearing designation and style letters of bearing desired (i.e. DL or DLG)

Tolerance for 7613™ and larger is +0.0001-0.0005 (+0.001-0.015)

Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear

Weights given are for greased and sealed versions

All bearing designations listed herein are trademarks of RBC Nice® Bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3616060473455
Diametro interno	22.23 mm
Diametro esterno	33.17 mm
Spessore	15.88 mm
Peso	200 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE