


Accessorio de supporti 7617-DL-NICE - 7617-DL-NICE

<https://www.123cuscinetti.ch/cuscinetti-supporti/supporti/accessorio/7617-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring (con't) **NICE®**

- PRECISION GRINDING ON ALL CONTACT SURFACES
- EASY TO USE DIMENSIONS
- MEDIUM LOADS
- HIGH SPEED RANGE: 5000 - 8000 RPM
- PRECISION MOUNTING
- SHOCK RESISTANT
- WIDER CASE STAGERS
- SHOCK RESISTANT STAGERS
- IDEALLY APPLICABLE ANGULAR CONTACT BEARING
- AVAILABLE SINGLE RINGS OR OPEN
- EXTENDED INNER RING WITH KEY GROOVES
- ALL BEARINGS HAVE A SHIP END SURFACE, WITH POLE ORIENTED TO AN EXTENDED INNER RING SURFACE
- RECOMMENDED FOR APPLICATIONS WHERE WEIGHT, SIZE, PRECISION AND SPEEDY MOUNTING ARE NECESSARY



BEARING Ø	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)		F (in) (mm)	G (in) (mm)
7617™ Ø	1.0625 26.99	2.5425 65.03	0.7500 19.05	0.0625 1.59	1.8750 42.47	0.1900 4.83

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C (lb) (N)	Static C ₀ (lb) (N)	W (kg)
0.085 1.65	2.788 70.25	1.417 35.99	0.605 15.37	0.261 6.63	1/4-28	0.035 0.89	5360 23852	2620 11659	0.84 0.38

① When ordering please indicate bearing designation and style letters of bearing desired (i.e. DL or DLG)
② Tolerance for 7613™ and larger is +.0000/-0.0005 (+.0001/-0.015)
③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
④ Weights given are for greased and sealed versions
All bearing designations listed herein are trademarks of RBC Nice® Bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3616060473486
Diametro interno	26.99 mm
Diametro esterno	42.47 mm
Spessore	19.05 mm
Peso	380 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE