


# Accessorio de supporti ER10-NICE - ER10-NICE

<https://www.123cuscinetti.ch/cuscinetti-supporti/supporti/accessorio/er10-nice>

**ER** Series Precision Ground Radial Bearings with **NICE**  
Extended Inner Ring and Metric Outside Diameter

- EXCLUSIVE, HEAVY DUTY "NICE" BEALS
- PERMANENTLY SEALED AND PRELUBRICATED FOR LONG LIFE
- STEEL YIELD GUARD AND INNER RING LUBRICATION GROOVES PROVIDE SUPERIOR PROTECTION
- BETTER PROTECTION IN EXTREME ENVIRONMENTS
- OPTIONAL LIP FORK SEAL IS AVAILABLE
- TWO LUBRICATION HOLES ALLOW FOR RE-GREASING
- TWO KNURLED OIL POINT SET SCREWS OFFER EXCELLENT RESISTANCE TO LOSING OIL UNDER VIBRATORY CONDITIONS
- FULLY GRINDING, SAE 52100 CHROME ALLOY STEEL RACES
- BLACK EDGE FINISH PROVIDES ADDITIONAL RESISTANCE



PRINCIPLE DIMENSIONS														
BASIC BEARING NUMBER	SHAFT Ø	OD	WIDTH		C	D	E	F	G	H	J	K	M	RADIUS
	(in)	(in)	A (in)	B (in)	(in)	(in)	(in)	(in)	(in)	(in)	(in)	(in)	(in)	(in)
ER10	5/8	1.8504	1/32	13/32	13/16	31/64	1/16	9/64	3/64	3/32	3/16	5/8	0.040	
	15.88	47	26.35	77.92	8.17	12.30	28.18	5.67	1.19	2.38	4.76	15.88	1.02	

RADIAL CAPACITY														
Ø	P	3-SET SCREWS	BASIC LOAD		REVOLUTIONS PER MINUTE								W	
			RATING C	RATING Co	50	150	300	500	1200	1800	2500	5000		
(in)	(in)		(N)	(N)	(N)	(N)	(N)	(N)	(N)	(N)	(N)	(N)	(N)	(kg)
0.094	2 1/16	10-32	2890	1480	921	638	508	427	319	278	250	198	0.56	
2.39	52.39		12527	6368	4098	2839	2292	1760	1429	1297	1113	881	0.25	

ⓘ Shaft tolerance +.0002/-0.0005 (+.0002/-0.13)    Ⓜ For low torque version add suffix "SPF"

## CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3663952560830
Diametro interno	15.88 mm
Diametro esterno	28.18 mm
Spessore	15.88 mm
Peso	250 g
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE