

## Accessorio de supporti N6910-NICE - N6910-NICE

<https://www.123cuscineti.ch/cuscineti-supporti/supporti/accessorio/n6910-nice>

**6900** Series™ Semi-Ground Radial Bearings, Extended Inner with Flanged Housing **NICE**

**EASY TO USE DIMENSIONS**

- MEDIUM LOADS
- MAX SPEED RANGE: 2000 - 3000 RPM
- THROUGH HARDENED
- RETAINED DESIGN
- NYLON RETAINER STANDARD
- DOUBLE SEALER STANDARD
- EXTENDED INNER RING WITH TWO SET SCREWS
- BEARINGS ARE AVAILABLE WITH OR WITHOUT FLANGES

BEARING		PRINCIPLE DIMENSIONS							
FLANGED UNIT	BEARING ONLY	Bore d (in)	O.D. D (in)	Width B (in)	Width C (in)	E (in)	F (in)	G (in)	H (in)
		+0.005	+0.000	+0.000	+0.000				
		+0.13	+0.00	+0.00	+0.00				
		-0.000	-0.005	-0.000	-0.000				
		-0.00	-0.15	-0.15	-0.15				
N6910™	B	0.625	1.6250	0.500	1.000	0.955	0.500	2.875	3.750
		15.875	41.28	12.70	25.40	24.26	12.70	73.03	95.25

PRINCIPLE DIMENSIONS								BASIC LOAD RATINGS		WEIGHT
J (in)	K (in)	L (in)	M (in)	N (in)	O 2-Set Screws	P (in)	S (in)	C (lbs)	C <sub>0</sub> (lbs)	W (kg)
0.875	0.438	0.688	1.000	0.062	1/4-28	0.4375	0.010	1610	1010	0.32
22.13	11.11	17.48	25.40	1.57		11.11	0.25	7165	4495	0.15

When Ordering specify whether assembly or bearing only is required. Bearings are stamped with designation and suffix B, for example 6904™B. Housings no longer carry part numbers.

Tolerance for 6912 and larger is +.0000/-0.0006 (+000/-016) Weights given are for greased and sealed version with flange mount.

## CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3616060473660
Diametro interno	15.875 mm
Diametro esterno	41.28 mm
Spessore	12.7 mm
Imballaggio	1

[contatto@123cuscineti.ch](mailto:contatto@123cuscineti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE