



Teste a snodo TSM MX-06-5-DUNLOP - MX-06-5-DUNLOP

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/tsm/mx-06-5-dunlop>

MALE ROD ENDS 



MALE ROD ENDS

MX SERIES

Description:
MX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

Material Specifications:
Housing: B17M 40, heat treated to 85/90 tons/m² tensile, Phosphated all over.
Ball: 100Cr 6, heat treated, Phosphated all over.

Features:
Metric and imperial sizes available
Can be used in application involving shock loading and high frequency oscillation.

Possible Applications:
Medium / heavy industrial/mechanical applications
Construction equipment
Agricultural equipment and motor sport.

Temperature Range:
-40°C to +150°C

Specification:
ELV & RoHS compliant

Housing: Forged B17M40, Heat Treated to 85/90 tons/m² tensile and Phosphate all over. **Balls:** Bearing Steel 100Cr6, Heat Treated and Phosphate all over.

Part No. Right Hand	Part No. Left Hand	B	W	H	O	D	F	A	M	X	Static Load Rating (Newtons) Radial
MX-06-5		.276	.237	.275	.437	.937	1.875	1.250	3/8 UNF	21	19610

Interchange table

Dunlop	Rose	NMB
MX-M (Metric)	R03-M	R03-M
MX (Imperial)	R03	R03

Note: Manufacturer's part numbers are used for descriptive purposes only and may not be direct equivalent products.
'0' in part number denotes grease nipple is fitted.

CARATTERISTICHE DEL PRODOTTO

Marchio	DUNLOP
N° Ean13	3616060550712
Diametro interno	7.937 mm
Diametro esterno	23.799 mm
Spessore	11.099 mm
Tipo	TSM
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1
Standard	Nessuno standard

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE