

Teste a snodo SI FX-10-G-DUNLOP - FX-10-G-DUNLOP

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/fx-10-g-dunlop>

FEMALE ROD ENDS 



FX SERIES

Description:
FX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

Material Specifications:
Housing: S17M 4J, heat treated to 80/90 tons/in² tensile, Phosphated all over. Ball: 100Cr 6, heat treated, Phosphated all over.

Features:
Metric and Imperial sizes available. Can be used in application involving shock loading and high frequency oscillation.

Possible Applications:
Medium / heavy industrial/mechanical applications. Construction equipment. Agricultural equipment and motor sport.

Temperature Range:
-40°C to +150°C

Specification:
ELV & RoHS compliant

Housing: Forged S17M4J, Heat Treated 80/90 tons/in² tensile and Phosphated all over. Ball: Bearing Steel 100Cr6, Heat Treated and Phosphated all over.

Part No. Right Hand	Part No. Left Hand	B	W	H	O	D	F	A	J	M	X	Static Load Rating (Newton) Radial
FX-10G		6250	875	750	875	1.937	2.625	1.375	1.000	3/8 UNF	21	77470

Interchange table

Dunlop	Rose	NMB
FX-M (Metric)	RBJ-M	RBJ-M
FX (Imperial)	RBJ	RBJ

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

CARATTERISTICHE DEL PRODOTTO

Marchio	DUNLOP
N° Ean13	3616060555304
Diametro interno	6250 mm
Diametro esterno	875 mm
Spessore	750 mm
Tipo	SI
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE