

Teste a snodo SI
FSLX-12-10-DUNLOP - FSLX-12-10-DUNLOP

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/fslx-12-10-dunlop>

FEMALE ROD ENDS



FSLX SERIES

Description:
FSLX series is for 3-piece steel on steel high strength range of female rod ends designed for motorsport and heavy industrial mechanical load applications. Incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and heavy mechanical load applications requiring low friction, available in both metric and imperial bore and thread sizes, they do not require maintenance.

Material Specifications:
Housing: Steel 708M40, heat treated, zinc plated and clear trivalent passivate. Inner Ring: Steel 670M20, zinc plated and clear trivalent passivate and stainless steel 304C. Liner: High strength PTFE bronze mesh composite. Ball: 100Cr6 heat treated, polished and electroless nickel plated and stainless steel 440C.

Features:
Metric & imperial thread & bore sizes, low friction, heavy duty, high shock loads, extended wear life, no maintenance.

Temperature Range:
-200°C to +260°C

Specifications:
ELV & RoHS compliant

Possible Applications:
Motorsport and heavy industrial mechanical applications.

Shaded option

Housing: Steel 708M40, Heat Treated, Zinc Plated and Clear Trivalent Passivate

Inner Ring: Steel 670M20, Zinc Plated and Clear Trivalent Passivate

Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Liner: High Strength PTFE Composite

Temp Range: -200°C to +260°C

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	AF	Static Load Rating (Newtons) Radial
FSLX-12-10		5/8	3/4 UNF	0.875	0.687	2.000	2.875	1.750	1.000	92500

Interchange table

Dunlop	Aurora	Fluro
FSLX-M (Metric)	AW-M-T and AG-M-T	GUSW
FSLX (Imperial)	AW-T and AG-T	

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

CARATTERISTICHE DEL PRODOTTO

Marchio	DUNLOP
N° Ean13	3616060556226
Diametro interno	15.875 mm
Diametro esterno	50.8 mm
Spessore	22.225 mm
Tipo	SI
Il filo	Filetto sinistro
Lubrificazione	NA
Carico statico	93.5 kN
Imballaggio	1

contatto@123cuscinetti.ch
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE