

## Teste a snodo SI FSX-04-DUNLOP - FSX-04-DUNLOP

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/fsx-04-dunlop>

**FEMALE ROD ENDS**



**DESCRIPTION:**  
FSX series is two 3-piece steel on steel high strength range of female rod ends designed for motorsport and heavy industrial, mechanical load applications. Incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and heavy mechanical load applications requiring low friction, available in both metric and imperial bore and thread sizes, they do not require maintenance.

**MATERIAL SPECIFICATIONS:**  
Housing: Steel 708M40, Heat Treated, Zinc Plated and Clear Trivalent Passivate  
Inner Ring: Steel 070M20, Zinc Plated and Clear Trivalent Passivate  
Ball: 100Cr6 Heat Treated, polished and electroless Nickel plated and stainless steel 440C  
Liner: High Strength PTFE Composite

**TEMPERATURE RANGE:**  
-200°C to +240°C

**FEATURES:**  
Metric & Imperial thread & bore sizes, low friction, heavy duty, high shock loads, extended wear life, no maintenance.

**POSSIBLE APPLICATIONS:**  
Motorsport and heavy industrial mechanical applications.

**SPECIFICATIONS:**  
ELV & RoHS compliant applications.

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	AF	Static Load Rating (Newtons) Radial
FSX-04		1/4	1/4 UNF	0.375	0.281	0.812	1.312	0.750	0.375	14700

**Interchange table**

Dunlop	Aurora	Fluro
FSX-M (Metric)	AM-M-T and AD-M-T	GUSW
FSX (Imperial)	AM-T and AD-T	

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

## CARATTERISTICHE DEL PRODOTTO

Marchio	DUNLOP
N° Ean13	3616060556295
Diametro interno	6.35 mm
Diametro esterno	20.6248 mm
Spessore	9.525 mm
Tipo	SI
Il filo	Filetto destro
Lubrificazione	NA
Carico statico	16.7 kN
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE