

## Snodi sferici GE

### GE140-ES-2RS-DUNLOP - GE140-ES-2RS-DUNLOP

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/ge/ge140-es-2rs-dunlop>

SPHERICAL BEARINGS




**GE ES SERIES**

**Description:**  
GE ES-Series is our 2-piece fractured outer ring metric range of spherical plain bearings used in non rotational applications. Ball and race sliding surfaces are treated with MoS<sub>2</sub> for increased lubricity on wear surface. A lubrication groove is provided on the raceway for applications requiring re-lubrication after installation.

**Material Specifications:**  
Outer ring: Bearing steel 100Cr6, case hardened and manganese phosphated, treated with MoS<sub>2</sub>. Ball: Bearing steel 100Cr6, case hardened and manganese phosphated. Seals: Polyurethane.

**Features:**  
Metric bore sizes  
Low cost  
Maintenance required  
Up to 140mm bore sizes available

**Possible Applications:**  
Light to heavy industrial mechanical applications  
Construction equipment  
Agricultural equipment  
hydraulic applications

**Temperature Range:**  
-24°C to +121°C

**Specifications:**  
ELV & RoHS compliant



**Outer Ring:** Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate, wear faces treated with MoS<sub>2</sub>.

**Ball:** Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate

**Seals:** Polyurethane

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
	GE140ES-2RS	140	90	70	210	5,400,000

## CARATTERISTICHE DEL PRODOTTO

Marchio	DUNLOP
N° Ean13	5059161173202
Diametro interno	140 mm
Diametro interno	5.512" inch
Diametro esterno	210 mm
Diametro esterno	8.268" inch
Spessore	90 mm
Spessore	3.543" inch
Tipo	GE
Lubrificazione	con
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE