

Snodi sferici GE GE300-ES-2RS-DUNLOP - GE300-ES-2RS-DUNLOP

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/ge/ge300-es-2rs-dunlop>

SPHERICAL BEARINGS 



GEZ ES SERIES

Description:
GEZ-ES-Series is our 2-piece fractured outer ring metric range of spherical plain bearings used in non rotational applications. Ball and race sliding surfaces are treated with MoS₂ for increased lubricity on wear surface. A lubrication groove is provided on the raceway for applications requiring re-lubrication after installation.

Material Specifications:
Outer ring: Bearing steel 100Cr6, case hardened and manganese phosphated, treated with MoS₂. Ball: Bearing steel 100Cr6, case hardened and manganese phosphated. Seals: Polyurethane.

Features:
Metric bore sizes
Low cost
Maintenance required
Up to 140mm bore sizes available

Possible Applications:
Light to heavy industrial/mechanical applications
Construction equipment
Agricultural equipment
Hydraulic applications

Temperature Range:
-34°C to +121°C

Specifications:
ELV & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate, wear faces treated with MoS₂.

Ball: Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate

Seals: Polyurethane

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
	GEZ300ES-2RS	3	66.675	57.150	120.65	1,500,000



CARATTERISTICHE DEL PRODOTTO

Marchio	DUNLOP
N° Ean13	3616060558312
Diametro interno	76.2 mm
Diametro interno	3" inch
Diametro esterno	120.65 mm
Diametro esterno	4 3/4" inch
Spessore	66.67 mm
Spessore	2.625" inch
Tipo	GE
Peso	3100 g
Lubrificazione	con
Imballaggio	-
Standard	Nessuno standard

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE