

Snodi sferici GE GE15-UK-DUNLOP - GE15-UK-DUNLOP

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/ge/ge15-uk-dunlop>

SPHERICAL BEARINGS 



Outer Ring: Bearing Steel 100Cr6, Case Hardened

GE UK SERIES

Description:
GE UK Series is our 2-piece metric range of general purpose spherical plain bearings incorporating a thin PTFE fabric between the ball and the outer ring, suitable for high shock loads and medium to heavy industrial/mechanical load applications requiring low friction. They do not require maintenance.

Material Specifications:
Outer ring: Bearing steel 100Cr6 and stainless steel 316, case hardened.
Ball: Bearing steel 100Cr6 case hardened and electro-less nickel plated and stainless steel 440C. Liner: High temperature PTFE composite.
Seals: Polyurethane.

Features
Metric bore sizes
Low friction
High shock loads
Extended wear life
No maintenance

Possible Applications
Medium-heavy industrial mechanical applications
Construction equipment
Agricultural equipment
Recreational vehicles
High precision motion control

Temperature Range
-200°C to +260°C
Specification
ELV & RoHS compliant

Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Liner: High Temperature PTFE Composite

| Part No. Unsized | Part No. Sized | Bore Size | W | H | D | Static Load Rating (Newtons) Radial |
|------------------|----------------|-----------|----|---|----|-------------------------------------|
| GE15UK | | 15 | 12 | 9 | 26 | 45,000 |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|----------------|
| Marchio | DUNLOP |
| N° Ean13 | 5059161173240 |
| Diametro interno | 15 mm |
| Diametro esterno | 26 mm |
| Spessore | 12 mm |
| Tipo | GE |
| Il filo | Filetto destro |
| Lubrificazione | con |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE