

## Snodi sferici GE GE110-UK-DUNLOP - GE110-UK-DUNLOP

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/ge/ge110-uk-dunlop>

SPHERICAL BEARINGS 



**SPHERICAL BEARINGS**




**GE UK SERIES**

**Description:**  
GE UK Series is our 2-piece metric range of general purpose spherical plain bearings incorporating a thin PTFE fabric between the ball and the outer ring, suitable for high shock loads and medium to heavy industrial/mechanical load applications requiring low friction. They do not require maintenance.

**Material Specifications:**  
Outer ring: Bearing steel 100Cr6 and stainless steel 316, case hardened.  
Ball: Bearing steel 100Cr6 case hardened and electro-less nickel plated and stainless steel 440C. Liner: High temperature PTFE composite.  
Seals: Polyurethane.

**Features**  
Metric bore sizes  
Low friction  
High shock loads  
Extended wear life  
No maintenance

**Possible Applications**  
Medium-heavy industrial mechanical applications  
Construction equipment  
Agricultural equipment  
Recreational vehicles  
High precision motion control

**Temperature Range**  
-200°C to +260°C  
**Specification**  
ELV & RoHS compliant

**Outer Ring:** Bearing Steel 100Cr6, Case Hardened     **Ball:** Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated  
**Liner:** High Temperature PTFE Composite

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
GE110UK		110	70	55	160	1,840,000

### CARATTERISTICHE DEL PRODOTTO

Marchio	DUNLOP
N° Ean13	3616060558749
Diametro interno	110 mm
Diametro interno	4.331" inch
Diametro esterno	160 mm
Diametro esterno	6.299" inch
Spessore	70 mm
Spessore	2.756" inch
Tipo	GE
Lubrificazione	con
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE