

## Gusci a rullini TAM1916-IKO - TAM1916-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/tam1916-iko>



Boundary dimensions		Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed (1)	Assembled inner ring
mm		mm				C	CF		
<i>Pw</i>	<i>D</i>	<i>C</i>	<i>z</i>	<i>z</i>	<i>z</i>	<i>M</i>	<i>H</i>	<i>K</i>	<i>rpm</i>
			Max.	Min.	Max.	Min.			
19	27	16	1.3	19.000	18.987	27.012	26.991	—	—
								12200	15700
								20000	RT 1916-1

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3616060599049
Diametro interno	19 mm
Diametro esterno	27 mm
Spessore	16 mm
Velocità limite	20000 rpm
Carico dinamico	12.2 kN
Carico statico	15.7 kN
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE