

## Gusci a rullini BA1820-Z-IKO - BA1820-Z-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/ba1820-z-iko>



Boundary dimensions mm[inch]			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed	Assembled inner ring
$F_w$	$D$	$C$	$d_2$	Shaft dia. Int.	Housing bore dia. Min.	Housing bore dia. Max.	$C$	$C_0$	rpm	
28.575 (1.124)	34.925 (1.375)	31.75 (1.250)	2.8	28.575	28.562	34.939	34.914	25700	52900	13000 (RB 1420)

### CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3616060601285
Diametro interno	28.575 mm
Diametro esterno	34.925 mm
Spessore	31.75 mm
Velocità limite	13000 rpm
Carico dinamico	25.7 kN
Carico statico	53.9 kN
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE