

## Gusci a rullini BA2420-Z-IKO - BA2420-Z-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/ba2420-z-iko>



Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed(I)	Assembled inner ring
$F_w$	$D$	$C$	$d_2$	$h_6$	$H_7$	$C$	$C_0$	rpm		
			Min.	Max.	Min.	Max.	Min.	Max.	IKO:RB 2420	
38.100 (1.1247405 (1 & 8))	47.625 (1.7175196)	31.75 (1.250)	38.1	47.625	47.625	39000	74200	9000		

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3616060601476
Diametro interno	38.1 mm
Diametro esterno	47.625 mm
Spessore	31.75 mm
Velocità limite	9000 rpm
Carico dinamico	39 kN
Carico statico	74.2 kN
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE