

Rondelle ondulate a filo tondo WSRW-28.58-3-1.52 - WSRW-28.58-3-1.52

<https://www.123cuscinetti.ch/accessori/rondella/ondulate/wsrw-28.58-3-1.52>

Do = Outside diameter (max) (mm)
Di = Inside diameter (min) (mm)
t = Thickness (mm)
H = Free height approx.
H1 = Load at height
L1 = Load at L1 (+/-15 % Newton)
DB = Bearing's outside diameter
Dh = Free fit in hole diameter
Dr = Free fit over hole diameter
N/Wx = Number of waves
PF = Load at flat (approx.)
d = Wire diameter



Wave Springs - Round Wire

Part Number	Wx	Lo (mm)	L1 (mm)	Dr (mm)	Dh (mm)	d (mm)	P1 (N)
RW-0112	3	3,23	2,59	24,56	28,58	1,52	445

CARATTERISTICHE DEL PRODOTTO

Marchio	GEN
Numero di ondulazioni	3
Altezza libera	3.23 mm
Imballaggio	1
Altezza di carico	2.59
Gioco sul diametro dell'albero	24.56 mm
Funziona in un alloggiamento di diametro	28.58 mm
Diametro del filo	1.52 mm

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE