

## Cuscinetti conico 30308-XR-JTEKT - 30308-XR-JTEKT

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/conico/30308-xr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.				
40	90	25.25	23	20	2	1.5	87.3	98.5	4 600	6 100	30308XR			
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1</sub> min.	d <sub>2</sub> max.	D <sub>1</sub> max.	D <sub>2</sub> min.	S <sub>1</sub> min.	S <sub>2</sub> min.	r <sub>1</sub> min.	r <sub>2</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
—	23.8	50	53	80	72	84	3	5	2	1.5	0.55	1.10	0.60	0.780

## CARATTERISTICHE DEL PRODOTTO

Marchio	JTEKT
N° Ean13	3663952404912
Diametro interno	40 mm
Diametro esterno	90 mm
Spessore	25.25 mm
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE