


## Cuscinetti conico 30315-DR-JTEKT - 30315-DR-JTEKT

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/conico/30315-dr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



| Boundary dimensions (mm)               |                    |                          |                      | Basic load ratings (kN) |                      |                      |                      | Limiting speeds (min <sup>-1</sup> ) |                      | Bearing No. <sup>1)</sup> |                    |                |                      |      |
|--|--------------------|--------------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|----------------------|---------------------------|--------------------|----------------|----------------------|------|
| d                                      | D                  | T                        | B                    | C                       | r <sub>1</sub>       | r <sub>2</sub>       | C <sub>r</sub>       | C <sub>0r</sub>                      | Grease lub.          |                           | Oil lub.           |                |                      |      |
| 75                                     | 160                | 40                       | 37                   | 28                      | 3                    | 2.5                  | 222                  | 266                                  | 2 100                | 2 900                     | 30315DR            |                |                      |      |
| Dimension series to ISO 955 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) |                      |                         |                      |                      |                      |                                      |                      | Constant e                | Axial load factors |                | (Refer. 1) Mass (kg) |      |
|  |                    | d <sub>1a</sub> min.     | d <sub>1a</sub> max. | D <sub>1a</sub> max.    | D <sub>1a</sub> min. | S <sub>1a</sub> min. | S <sub>1a</sub> max. | r <sub>1a</sub> min.                 | r <sub>1a</sub> max. |                           | Y <sub>1</sub>     | Y <sub>0</sub> |                      |      |
| —                                      | 48.8               | 89                       | 91                   | 148                     | 127                  | 151                  | 6                    | 14                                   | 2.5                  | 2                         | 0.81               | 0.74           | 0.41                 | 3.48 |

## CARATTERISTICHE DEL PRODOTTO

|                  |               |
|------------------|---------------|
| Marchio          | JTEKT         |
| N° Ean13         | 4549250122149 |
| Diametro interno | 75 mm         |
| Diametro esterno | 160 mm        |
| Spessore         | 40 mm         |
| Peso             | 3516 g        |
| Imballaggio      | 1             |

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE