


## Cuscinetti conico 32320-JR-JTEKT - 32320-JR-JTEKT

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/conico/32320-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



| Boundary dimensions (mm)               |                    |                          |                      | Basic load ratings (kN) |                      |                      |                      | Limiting speeds (min <sup>-1</sup> ) |                      | Bearing No. <sup>1)</sup> |                    |                |                      |      |
|--|--------------------|--------------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|----------------------|---------------------------|--------------------|----------------|----------------------|------|
| d                                      | D                  | T                        | B                    | C                       | C <sub>r</sub>       | C <sub>0r</sub>      | Grease lub.          | Oil lub.                             |                      |                           |                    |                |                      |      |
| 100                                    | 215                | 77.5                     | 73                   | 60                      | 579                  | 783                  | 1 800                | 2 400                                | 32320JR              |                           |                    |                |                      |      |
| Dimension series to ISO 955 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) |                      |                         |                      |                      |                      |                                      |                      | Constant e                | Axial load factors |                | (Refer. 1) Mass (kg) |      |
|  |                    | d <sub>1a</sub> min.     | d <sub>1a</sub> max. | D <sub>1a</sub> min.    | D <sub>1a</sub> max. | S <sub>1a</sub> min. | S <sub>1a</sub> max. | r <sub>1a</sub> min.                 | r <sub>1a</sub> max. |                           | Y <sub>1</sub>     | Y <sub>0</sub> |                      |      |
| 26D                                    | 53.9               | 118                      | 123                  | 201                     | 177                  | 200                  | 8                    | 17.5                                 | 3                    | 2.5                       | 0.35               | 1.74           | 0.96                 | 13.0 |

## CARATTERISTICHE DEL PRODOTTO

|                  |               |
|------------------|---------------|
| Marchio          | JTEKT         |
| N° Ean13         | 3663952410623 |
| Diametro interno | 100 mm        |
| Diametro esterno | 215 mm        |
| Spessore         | 77.5 mm       |
| Imballaggio      | 1             |

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE