

Cuscinetti conico 679-672-JTEKT - 679-672-JTEKT

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/conico/679-672-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|---------|--------|--------|--------|---------------|---------------|-------------------------|----------|--------------------------------------|----------|
| d | D | T | B | C | r_a max. | r_b min. | C_r | C_{10} | Grease lub. | Oil lub. |
| 88.900 | 168.275 | 41.275 | 41.275 | 30.162 | 3.6 | 3.2 | 224 | 349 | 2 200 | 3 000 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | Constant | Axial load factors | | (Refer.) Mass (kg) | | |
|-------------|------------|------------------|--------------------------|-------|-------|-------|---------------|---------------|--------------------|-------|--------------------|------------|------------|
| Inner ring | Outer ring | a | d_a | d_b | D_a | D_b | r_a max. | r_b max. | e | Y_1 | Y_2 | Inner ring | Outer ring |
| 679 | 672 | 38.6 | 107.0 | 101.0 | 149.0 | 160.0 | 3.6 | 3.2 | 0.47 | 1.28 | 0.70 | 2.75 | 1.22 |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | JTEKT |
| N° Ean13 | 3663952429625 |
| Diametro interno | 88.9 mm |
| Diametro esterno | 168.275 mm |
| Spessore | 41.275 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE