


## Cuscinetti a rullini BHTM916-JTEKT - BHTM916-JTEKT

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/bhtm916-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.		Caged type	
9	16	16	13.3	7.95	7.90	32 000		With open ends	With closed end

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	8.991	9.000	15.977	15.995	12	13

## CARATTERISTICHE DEL PRODOTTO

Marchio	JTEKT
N° Ean13	3663952469485
Diametro interno	9 mm
Diametro interno	0.354" inch
Diametro esterno	16 mm
Diametro esterno	0.63" inch
Spessore	16 mm
Spessore	0.63" inch
Peso	12 g
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE