


Cuscinetti a rullini 16MKM2212-JTEKT - 16MKM2212-JTEKT

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/16mkm2212-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F_w	D	C	b min.	C_{10}	C_{50}	Oil lub.	Caged type	With closed end
16	22	12	9.3	7.80	9.80	22 000	With open ends	16MKM2212

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	15.989	16.000	21.991 ⁴⁾	22.012 ⁴⁾	11	12

CARATTERISTICHE DEL PRODOTTO

Marchio	JTEKT
N° Ean13	3663952470290
Diametro interno	16 mm
Diametro interno	0.63" inch
Diametro esterno	22 mm
Diametro esterno	0.866" inch
Spessore	12 mm
Spessore	0.472" inch
Peso	12 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE