


Cuscinetti a rullini BHTM1616A-JTEKT - BHTM1616A-JTEKT

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/bhtm1616a-jtekt>

Drawn cup needle roller bearings 



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|-----|-----|-------------|-------------------------|----------|--------------------------------------|----------------------------------------------|
| F_w | D | C | b min. | C_0 | C_{0r} | Oil lub. | Caged type With open ends With closed end |
| 16 | 24 | 16 | 13.3 | 12.2 | 14.9 | 21 000 | BHTM1616A |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|--------------------------------|----------------------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (f6) min. | max. | Housing bore dia. (H7) min. | max. | With open ends | With closed end |
| — | — | 15.989 | 16.000 | 23.991 ⁴⁾ | 24.012 ⁴⁾ | 20 | 23 |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | JTEKT |
| N° Ean13 | 3663952470368 |
| Diametro interno | 16 mm |
| Diametro esterno | 24 mm |
| Spessore | 16 mm |
| Peso | 20 g |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE