


Cuscinetti a rullini BTM172425-JTEKT - BTM172425-JTEKT

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/btm172425-jtekt>

Drawn cup needle roller bearings 



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | |
|--------------------------|----|----|--------|-------------------------|-----------------|--------------------------------------|----------------|---------------------------|--|
| F _w | D | C | b min. | C ₀ | C _{0r} | Oil lub. | Caged type | | |
| | | | | | | | With open ends | With closed end | |
| 17 | 24 | 25 | — | 19.0 | 29.0 | 20 000 | BTM172425 | | |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|----------------------|-----------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (φ6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 16.983 ²⁾ | 16.994 ²⁾ | 23.972 | 23.993 | 22 | — |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | JTEKT |
| N° Ean13 | 3663952470542 |
| Diametro interno | 17 mm |
| Diametro interno | 0.669" inch |
| Diametro esterno | 24 mm |
| Diametro esterno | 0.945" inch |
| Spessore | 25 mm |
| Spessore | 0.984" inch |
| Peso | 22 g |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE