

Cuscinetti a rullini BTM2215-JTEKT - BTM2215-JTEKT

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/btm2215-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾		
F _w	D	C	b min.	C ₀	C _{0r}	Oil lub.	Caged type		
								With open ends	With closed end
22	29	15	—	12.0	18.3	16 000	BTM2215		

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6)		Housing bore dia. (N7)		With open ends	With closed end
		min.	max.	min.	max.		
—	—	21.987	22.000	28.972	28.993	22	—

CARATTERISTICHE DEL PRODOTTO

Marchio	JTEKT
N° Ean13	3663952471198
Diametro interno	22 mm
Diametro interno	0.866" inch
Diametro esterno	29 mm
Diametro esterno	1.142" inch
Spessore	15 mm
Spessore	0.591" inch
Peso	22 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE