

Cuscinetti a rullini BTM4025-JTEKT - BTM4025-JTEKT

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/btm4025-jtekt>

Drawn cup needle roller bearings 



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ |
|--------------------------|-----|-----|-------------------------|----------|--------------------------------------|-------------|---------------------------|
| F_w | D | C | C_0 | C_{0r} | Oil lub. | Grease lub. | |
| 40 | 50 | 25 | — | 36.2 | 66.2 | 9 100 | BTM4025 |

| Full complement type | | Recommended dimensions (mm) | | | | Refer. Mass (g) | |
|----------------------|-----------------|-----------------------------|----------------------|-----------------------------|-----------------------------|-----------------|-----------------|
| With open ends | With closed end | Shaft dia. (H6) min. | Shaft dia. (H6) max. | Housing bore dia. (H7) min. | Housing bore dia. (H7) max. | With open ends | With closed end |
| — | — | 39.984 | 40.000 | 49.967 | 49.992 | 91 | — |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | JTEKT |
| N° Ean13 | 3663952472621 |
| Diametro interno | 40 mm |
| Diametro esterno | 50 mm |
| Spessore | 25 mm |
| Peso | 91 g |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE