

Cuscinetti a rulli NN3016K-JTEKT - NN3016K-JTEKT

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/rulli/nn3016k-jtekt>

Double-row cylindrical roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min ⁻¹)		Bearing No.	
d	D	B	r _{min}	F _w	E ₀	C	C ₀₇	Grease lub.	Oil lub.	NN Cylindrical bore Tapered bore
80	125	34	1.1	—	113	119	166	4 800	5 800	NN3016K

		Mounting dimensions (mm)						(Refer.) Mass (kg)	
Cylindrical bore	Tapered bore	d _a		D _a		r _s		Cylindrical bore	Tapered bore
		min.	max.	min.	max.	min.	max.		
		86.5	—	—	118.5	114	1	1.55	1.50

CARATTERISTICHE DEL PRODOTTO

Marchio	JTEKT
N° Ean13	3663952473758
Diametro interno	80 mm
Diametro esterno	125 mm
Spessore	34 mm
Peso	1500 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE