

Cuscinetti a rulli NQ32-30-JTEKT - NQ32-30-JTEKT

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/rulli/nq32-30-jtekt>

Machined ring needle roller bearings 

F_w 29 ~ 37 mm

Without inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. |
|--------------------------|-------|-------|-------|-------------------------|-----------------|------------------------------------|--|--------------------|-------------|
| F_w | d | D | B | C_r | C_{10} | Oil lub. | | Without inner ring | |
| 32 | 28 | 42 | 30 | 34.4 | 61.8 | 14 000 | | NQ32/30 | |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | | |
| With inner ring | | | | Without inner ring | With inner ring | | | | |
| | d_a | D_a | r_a | 0.104 | 0.141 | | | | |
| | max. | max. | max. | | | | | | |
| | 30 | 40 | 0.3 | | | | | | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | JTEKT |
| N° Ean13 | 3663952482798 |
| Diametro interno | 32 mm |
| Diametro interno | 1.26" inch |
| Diametro esterno | 42 mm |
| Diametro esterno | 1.654" inch |
| Spessore | 30 mm |
| Spessore | 1.181" inch |
| Peso | 104 g |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE