

Cuscinetti a rulli 40NQ5230-JTEKT - 40NQ5230-JTEKT

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/rulli/40nq5230-jtekt>

Machined ring needle roller bearings 

F_w 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	r	C_r	C_{10}	Oil lub.	Without inner ring	
40	—	52	30	0.6	47.0	81.0	11 000	40NQ5230	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
	d_s	D_s	r_s	Without inner ring	With inner ring				
	min.	max.	max.	0.148	—				

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARATTERISTICHE DEL PRODOTTO

Marchio	JTEKT
N° Ean13	3663952483085
Diametro interno	40 mm
Diametro esterno	52 mm
Spessore	30 mm
Peso	148 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE