

Cuscinetti a rulli RNA49-48R-JTEKT - RNA49-48R-JTEKT

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/rulli/rna49-48r-jtekt>

Machined ring needle roller bearings 

F_w 29 ~ 37 mm

Without inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. Without inner ring |
|--------------------------|-----|-----|-----|-------------------------|-----------------|--------------------------------------|--|-----------|-----------------------------------|
| F_w | d | D | B | C_r | C_{10} | Oil lub. | Grease lub. | | |
| 55 | — | 70 | 22 | 46.9 | 76.5 | 8 300 | — | RNA49/48R | |
| Mounting dimensions (mm) | | | | (roller) Mass (kg) | | (roller) Applicable inner ring No. | | | |
| With inner ring | | | | Without inner ring | With inner ring | — | | | |
| — | | | | 66 | 0.6 | 0.174 | | | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | JTEKT |
| N° Ean13 | 3663952483481 |
| Diametro interno | 55 mm |
| Diametro esterno | 70 mm |
| Spessore | 22 mm |
| Peso | 174 g |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE