


## Gusci a rullini BA1418-ZOH-IKO - BA1418-ZOH-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/ba1418-zoh-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



BA--Z BHA--Z

Shaft dia. mm (inch)	Identification number			Standard Mass (Ref.) g	Closed end Mass (Ref.) g	Grease retained Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end			
22.225 (7/8)	---	---	---	<b>BA 1418 Z</b> 34.5	---	---

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring
F <sub>w</sub>	D	C	Shaft dia. h <sub>6</sub>	Housing bore dia. J7	Max.	Min.	N	N	rpm	
22.225   7/8	28.575   1 1/8	28.58   1.125	2.8	22.225   22.212	28.587	28.566	19 800	35 600	18 000	---

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952172774
Diametro interno	22.23 mm
Diametro esterno	28.58 mm
Spessore	28.58 mm
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE