



## Gusci a rullini BAM118-IKO - BAM118-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bam118-iko>

IKO  
SHELL TYPE NEEDLE ROLLER BEARINGS  
Inch Series

BAM BHAM

Shaft dia. mm (inch)	Identification number																
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g								
17.462 ( $\frac{3}{16}$ )	—	—	—	—	—	—	—	—	BAM 118	10.8	—	—					
Boundary dimensions		mm(inch)		Standard mounting dimensions				mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed <sup>(1)</sup>		Assembled inner ring	
$F_w$	$D$	$C$	$b_2$	Shaft dia. $h_8$	Housing bore dia. $J_7$	$C$	$C_0$	$C_0$	$N$	$N$	$N$	$N$	rpm				
17.462 ( $\frac{3}{16}$ )	22.225 ( $\frac{7}{8}$ )	12.701 (500)	1.3	17.462	17.451	22.237	22.216	6 140	8 850	25 000	IRB 88						

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952172996
Diametro interno	17.46 mm
Diametro esterno	22.23 mm
Spessore	12.7 mm
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE