


Gusci a rullini BAM1210-IKO - BAM1210-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bam1210-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
19.050 ($\frac{3}{4}$)	—	—	—	—	—	—	—	BAM 1210	18.6	—	—

Boundary dimensions			mm(inch)	Standard mounting dimensions				mm	Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_w	D	C	B	Shaft dia. ϕ_6	Housing bore dia. ϕ_7	Max.	Min.	C	C_0	n	rpm	IRB #10-1
19.050	25.400	15.881 (625)	1.3	19.050	19.037	25.412	25.391	9 500	13 200	20 000		

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952173009
Diametro interno	19.05 mm
Diametro esterno	25.4 mm
Spessore	15.88 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE