


## Gusci a rullini BAM1312-IKO - BAM1312-IKO

https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bam1312-iko



**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series

**BAM BHAM**

Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g	
20.638 ( $1\frac{1}{8}$ )	--	--	--	--	--	--	<b>BAM 1312</b>	23.5	--	--
Boundary dimensions mm(inch)		Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring	
$F_w$	D	C	$h_2$	Shaft dia. h6	Housing bore dia. J7	N	N	rpm	IRB 912	
20.638 $\pm$ .012	26.988 $\pm$ .012	19.051 $\pm$ .012	1.3	20.638 Max.	20.625 Min.	27.000 Max.	26.979 Min.	12 400	19 000	19 000

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952173078
Diametro interno	20.64 mm
Diametro interno	13/16" inch
Diametro esterno	26.99 mm
Diametro esterno	1 1/16" inch
Spessore	19.05 mm
Spessore	3/4" inch
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE