


Gusci a rullini BAM1320-IKO - BAM1320-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bam1320-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Identification number			Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end			
20.638 ($\frac{3}{16}$)	—	—	—	—	—	—	BAM 1320	37.5	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F _w	D	C	Shaft dia. h6	Housing bore dia. J7	Max.	Min.				
20.638 $\frac{3}{16}$	26.988 $1 \frac{1}{8}$	31.751 1.250	20.638	20.625	27.000	26.979	21 200	38 100	19 000	IRB 920

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952173108
Diametro interno	20.64 mm
Diametro esterno	26.99 mm
Spessore	31.75 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE