



Gusci a rullini BAM138-IKO - BAM138-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bam138-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

BAM BHAM

Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
20.638 ($\frac{3}{16}$)	—	—	—	—	—	—	—	BAM 138	16.4	—	—
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled inner ring	
F_w	D	C	B	Shaft dia. h6	Housing bore dia. J7	Max.	Min.	N	N	rpm	IRB 98
20.638	26.988	12.70	1.3	20.638	20.625	27.000	26.979	7 170	9 450	19 000	IRB 98

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952173122
Diametro interno	20.64 mm
Diametro esterno	26.99 mm
Spessore	12.7 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE