


Gusci a rullini BAM1510-IKO - BAM1510-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bam1510-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number													
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g					
23.812 ($\frac{9}{4}$)	—	—	—	—	—	—	—	BAM 1510	23	—	—			
Boundary dimensions mm(inch)			Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring					
<i>F_w</i>	<i>D</i>	<i>C</i>	<i>t</i> Max.	Shaft dia. h8 Max.	Housing bore dia. J7 Min.	N	N	rpm	IRB 1110					
23.812	$\frac{9}{4}$	30.162	$1\frac{1}{2}$	15.88	.625	2.8	23.812	23.799	30.176	30.151	11 000	17 100	16 000	IRB 1110

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952173207
Diametro interno	23.81 mm
Diametro esterno	30.16 mm
Spessore	15.88 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE