

## Gusci a rullini BAM186-IKO - BAM186-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bam186-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series

BAM BHAM

Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
<b>28.575</b> (1 1/8)	—	—	—	—	—	—	—	<b>BAM 186</b>	18.1	—	—
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring	
F <sub>w</sub>	D	C	t	Shaft dia. h <sub>s</sub>	Housing bore dia. J7	Max.	Min.	N	N	rpm	
28.575 (1 1/8)	34.925 (1 3/8)	9.52 (3/8)	2.8	28.575	28.562	34.939	34.914	6 330	8 910	13 000	—

Note<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952173368
Diametro interno	28.58 mm
Diametro esterno	34.93 mm
Spessore	9.52 mm
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE