


## Gusci a rullini BAM208-IKO - BAM208-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bam208-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g	
31.750 (1 1/4)	—	—	—	—	—	—	<b>BAM 208</b>	26	—	—

Boundary dimensions			Standard mounting dimensions			Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring
F <sub>w</sub>	D	C <sub>1</sub>	Shaft dia. h <sub>s</sub> Max.   Min.	Housing bore dia. J <sub>7</sub> Max.   Min.	mm				
31.750   1 1/4	38.100   1 1/2	12.70   .500	2.8	31.750   31.734	38.114   38.089	9 100	14 700	12 000	<b>IRB 168</b>

Note<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952173405
Diametro interno	31.75 mm
Diametro interno	1 1/4" inch
Diametro esterno	38.1 mm
Diametro esterno	1 1/2" inch
Spessore	12.7 mm
Spessore	1/2" inch
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE