



Gusci a rullini BAM45-IKO - BAM45-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bam45-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

BAM BHAM

Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
6.350 ($\frac{1}{4}$)	—	—	—	—	—	—	—	BAM 45	2.7	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_w	D	C	Shaft dia. h_8	Housing bore dia. J_7	C	C_0	C_0	rpm		
6.350 ($\frac{1}{4}$)	11.112 ($\frac{7}{16}$)	7.921 ($\frac{5}{16}$)	6.350 Max.	6.341 Min.	11.122 Max.	11.104 Min.	1 510	1 120	55 000	—

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952173412
Diametro interno	6.35 mm
Diametro esterno	11.11 mm
Spessore	7.92 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE