



## Gusci a rullini BAM77-IKO - BAM77-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bam77-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series

BAM BHAM

Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
11.112 ( $\frac{7}{16}$ )	—	—	—	—	—	—	—	<b>BAM 77</b>	6.2	—	—
Boundary dimensions mm(inch)		Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring		
$F_w$	$D$	$C$	$b_2$	Shaft dia. h8	Housing bore dia. J7	N	N	rpm	—		
11.112 ( $\frac{7}{16}$ )	15.875 ( $\frac{5}{8}$ )	11.131 (438)	1	11.112 Max.	11.101 Min.	15.885 Max.	15.867 Min.	4 150	4 680	35 000	—

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952173542
Diametro interno	11.11 mm
Diametro esterno	15.88 mm
Spessore	11.13 mm
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE