



## Gusci a rullini BAM96-IKO - BAM96-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bam96-iko>

IKO  
SHELL TYPE NEEDLE ROLLER BEARINGS  
Inch Series

BAM BHAM

Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
14.288 ( $\frac{9}{16}$ )	—	—	—	—	—	—	BAM 96	6.8	—

Boundary dimensions mm(inch)			Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring	
F <sub>w</sub>	D	C	Shaft dia. h8 Max.	Housing bore dia. J7 Min.	Max.	N	N	rpm		
14.288	19.050 ( $\frac{7}{8}$ )	9.52 ( $\frac{3}{8}$ )	14.288	14.277	19.062	19.041	3 850	4 560	30 000	—

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952173658
Diametro interno	14.29 mm
Diametro esterno	19.05 mm
Spessore	9.52 mm
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE